





- Exchangeable fiber glass filter insert
- Separation of the particles and liquid fractions
- Protection against injectors oily substances
- Improves the efficiency of the gas supply system

## **TECHNICAL SPECIFICATION:**

- 99% filtration efficacy for particles of 1  $\mu m$
- Max. pressure: 4.5 bar
- Temperature range: -20 [° C] to 120 [° C]
- Gas outlets: Ø 10.6 / 12 mm
- Dimensions: 120 mm x 110 mm x Ø 68 mm

## Perfect Blue volatile phase filter

TYPE: LPG volatile phase filter with oil fractions separation

**MODEL**: Perfect Blue

The volatile phase filter Perfect Blue efficiently separates all the impurities in the gas LPG. Assembly of the Perfect Blue filter effectively protects against oily substances and solid particles increasing the reliability of the whole gas installation.

## **INSTALLATION INSTRUCTION:**

The Perfect Blue should be assembled between the reducer and the gas pressure sensor, in an easily accessible place, to the vehicle's body, in the same direction as the gas flow, vertically and in a place that should not be exposed to high temperature (max. + 120 ° C).

## THE PERFECT BLUE REPLACEMENT FILTER SET INCLUDES:

- Filter cartridge (1)
- Gas wheel (2)
- Sealing o-ring (3)



LPGTECH Sp. z o. o., ul. Dojnowska 67, 15-557 Białystok